


BookletChart™


Portsmouth to Cape Ann

NOAA Chart 13278




A reduced-scale NOAA nautical chart for small boaters

When possible, use the full-size NOAA chart for navigation.



- Complete, reduced-scale nautical chart
- Print at home for free
- Convenient size
- Up-to-date with Notices to Mariners
- Compiled by NOAA's Office of Coast Survey, the nation's chartmaker



Published by the
National Oceanic and Atmospheric Administration
National Ocean Service
Office of Coast Survey
www.NauticalCharts.NOAA.gov
888-990-NOAA

What are Nautical Charts?

Nautical charts are a fundamental tool of marine navigation. They show water depths, obstructions, buoys, other aids to navigation, and much more. The information is shown in a way that promotes safe and efficient navigation. Chart carriage is mandatory on the commercial ships that carry America's commerce. They are also used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters.

What is a BookletChart™?

This BookletChart is made to help recreational boaters locate themselves on the water. It has been reduced in scale for convenience, but otherwise contains all the information of the full-scale nautical chart. The bar scales have also been reduced, and are accurate when used to measure distances in this BookletChart. See the Note at the bottom of page 5 for the reduction in scale applied to this chart.

Whenever possible, use the official, full scale NOAA nautical chart for navigation. Nautical chart sales agents are listed on the Internet at <http://www.NauticalCharts.NOAA.gov>.

This BookletChart does NOT fulfill chart carriage requirements for regulated commercial vessels under Titles 33 and 44 of the Code of Federal Regulations.

Notice to Mariners Correction Status

This BookletChart has been updated for chart corrections published in the U.S. Coast Guard Local Notice to Mariners, the National Geospatial Intelligence Agency Weekly Notice to Mariners, and, where applicable, the Canadian Coast Guard Notice to Mariners. Additional chart corrections have been made by NOAA in advance of their publication in a Notice to Mariners. The last Notices to Mariners applied to this chart are listed in the Note at the bottom of page 7. Coast Pilot excerpts are not being corrected.

For latest Coast Pilot excerpt visit the Office of Coast Survey website at <http://www.nauticalcharts.noaa.gov/nsd/searchbychart.php?chart=13278>.



(Selected Excerpts from Coast Pilot)

From Cape Elizabeth the coast of Maine continues southwestward for about 37 miles to the Piscataqua River and the deepwater port of Portsmouth, NH. The few harbors along this part of Maine are suited mostly to fishing vessels, yachts, and small pleasure craft. This is a summer-resort area, and many of the buildings are large and prominent. Two tall water tanks, one westward of Wood Island Light and one at Cape Porpoise Harbor, are the most

prominent objects between Portland and Portsmouth.

Extending south-southwestward from Portsmouth Harbor is the 13-mile coast of New Hampshire; the Isles of Shoals are 6 miles southeast of the

harbor. Southward and eastward from the New Hampshire line the extreme northern part of the Massachusetts coast extends about 23 miles to Cape Ann Light. The Merrimack River approach to Newburyport, MA is about 3 miles south of the New Hampshire boundary.

No-Discharge Zones.—The State of New Hampshire, with the approval of the Environmental Protection Agency, has established a No-Discharge Zone (NDZ) covering all coastal waters of New Hampshire, extending about 3 miles offshore (see chart 13278).

The State of Massachusetts, with the approval of the Environmental Protection Agency, has established a No-Discharge Zone (NDZ) in all coastal waters of Massachusetts described in this volume, extending about 3 miles offshore (see charts 13278 and 13267).

Within the NDZs, discharge of sewage, whether treated or untreated, from all vessels is prohibited. Outside the NDZs, discharge of sewage is regulated by **40 CFR 140** (see chapter 2).

From **Fox Hill Point** (42°57.9'N., 70°46.2'W.) to Merrimack River entrance, there are about 9 miles of sandy beaches, several rocky headlands, and offlying reefs and ledges up to 1 mile from shore. A large house with three chimneys on Fox Hill Point is very prominent. Summer resorts line the beaches, and hotels and prominent summer homes are on the headlands. Salt marshes between the beaches and the coastal ridge about 2 to 2.5 miles westward are drained by small rivers, most of which flow into the inlet at Hampton Harbor.

Little Boars Head is a yellow bluff 7 miles southwestward of Whaleback Light. A summer resort of the same name extends over 0.5 mile north-eastward from the bluff; a large mansion on the head is conspicuous. A ledge, awash at low water, is about 0.4 mile eastward of the head. A buoy, about 1 mile east-southeastward of the head, marks the ledge and the broken and foul ground off it.

Great Boars Head (42°55.1'N., 70°47.7'W.) is a bluff point making out 0.3 mile between North Beach and Hampton Beach, and 9.5 miles southwestward of Whaleback Light. The summer resort of **Hampton Beach** extends southward from the point.

Hampton Harbor, about 10 miles southwestward of Portsmouth Harbor and 1.5 miles southward of Great Boars Head, is an inlet formed by the confluence of **Hampton River** and **Blackwater River** and other rivers, sloughs, and creeks that drain the extensive area of salt marsh to the westward of Hampton, Seabrook, and Salisbury Beaches.

The harbor is principally an anchorage for numerous pleasure craft and a considerable number of party and charter hire fishing boats which operate from the harbor from late spring to early fall. There is also some year-round fishing activity.

The entrance to the inlet is between two rock jetties. The outer part of the south jetty is submerged. A daybeacon is on the north jetty, and a daybeacon is off the end of the south jetty.

Anchorage.—Anchorages are available in the basins or in the narrow channels of the Hampton and Blackwater Rivers and other rivers and creeks northward and southward of the inlet.

Dangers.—Extensive rocky ledges obstruct the approaches to the entrance to the inlet. **Hampton Shoal Ledge**, covered 19 feet, about 2.8 miles eastward of the entrance, is unmarked.

About 0.5 mile off the entrance is an extensive area of drying and covered rocky ledges consisting of **Old Cellar Rock**, **Inner Sunk Rocks**, **Outer Sunk Rocks**, and other rocks between Inner and Outer Sunk Rocks; a buoy is northeastward of the area.

U.S. Coast Guard Rescue Coordination Center **24 hour Regional Contact for Emergencies**

RCC Boston


Commander

1st CG District

Boston, MA

(617) 223-8555

Navigation Managers Area of Responsibility



NOAA's navigation managers serve as ambassadors to the maritime community.


They help identify navigational challenges facing professional and recreational mariners, and provide NOAA resources and information for safe navigation. For additional information, please visit nauticalcharts.noaa.gov/service/navmanagers

To make suggestions or ask questions online, go to nauticalcharts.noaa.gov/inquiry.

To report a chart discrepancy, please use ocsdata.ncd.noaa.gov/idrs/discrepancy.aspx.

Lateral System As Seen Entering From Seaward

on navigable waters except Western Rivers







For more information on aids to navigation, including those on Western Rivers, please consult the latest USCG Light List for your area.

These volumes are available online at <http://www.navcen.uscg.gov>

SOUNDINGS IN FEET

13278



Joins page 8


4


Note: Chart grid lines are aligned with true north.

Printed at reduced scale.


SCALE 1:80,000
Nautical Miles

See Note on page 5.





This BookletChart was reduced to 75% of the original chart scale.
The new scale is 1:106666. Barscales have also been reduced and
are accurate when used to measure distances in this BookletChart.



Joins page 5

Joins page 10


6


Note: Chart grid lines are aligned with true north.

Printed at reduced scale.


SCALE 1:80,000
Nautical Miles

See Note on page 5.





Last Correction: 3/31/2016. Cleared through:
 LNM: 2516 (6/21/2016), NM: 2716 (7/2/2016), CHS: 0616 (6/24/2016)




8


Note: Chart grid lines are aligned with true north.

Printed at reduced scale.


SCALE 1:80,000
Nautical Miles

See Note on page 5.





Joins page 7



become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging, or trawling.
Covered wells may be marked by lighted or unlighted buoys.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

CAUTION

Entrances to Inlets

The channels are subject to continual changes. Entrance buoys are not charted because they are frequently shifted in position.

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

CAUTION

BASCULE BRIDGE CLEARANCES



For bascule bridges, whose spans do not open to a full upright or vertical position, unlimited vertical clearance is not available for the entire charted horizontal clearance.

RACING BUOYS

Racing buoys within the limits of this chart are not shown hereon. Information may be obtained from the U.S. Coast Guard District Offices as racing and other private buoys are not all listed in the U.S. Coast Guard Light List.

Joins page 8

Federal Law Prohibits Landing on Refuge Beach



28th Ed., Aug. /13

13278

CAUTION

This chart has been corrected from the Notice to Mariners (NM) published weekly by the National Geospatial-Intelligence Agency and the Local Notice to Mariners (LNM) issued periodically by each U.S. Coast Guard district to the dates shown in the lower left hand corner. Chart updates corrected from Notice to Mariners published after the dates shown in the lower left hand corner are available at nauticalcharts.noaa.gov

Last Correction: 3/31/2016. Cleared through:
LNM: 2516 (6/21/2016), NM: 2716 (7/2/2016), CHS: 0616 (6/24/2016)

This nautical chart has been designed to promote safe navigation. Ocean Service encourages users to submit corrections, additions, or improvements to the Chief, Marine Chart Division (N/C52), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.


12


Note: Chart grid lines are aligned with true north.

Printed at reduced scale.

SCALE 1:80,000
Nautical Miles


See Note on page 5.





h. The National comments for National Ocean

Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY



Published at Washington, D.C.
U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SERVICE
COAST SURVEY

SOUNDINGS IN FEET

FATHOMS	FEET	METERS
1	6	1.1
2	12	2.2
3	18	3.3
4	24	4.4
5	30	5.5
6	36	6.6
7	42	7.7
8	48	8.8
9	54	9.9
10	60	11.0
11	66	12.1
12	72	13.2
13	78	14.3
14	84	15.4
15	90	16.5
16	96	17.6
17	102	18.7
18	108	19.8
19	114	20.9
20	120	22.0
21	126	23.1
22	132	24.2
23	138	25.3
24	144	26.4
25	150	27.5
26	156	28.6
27	162	29.7
28	168	30.8
29	174	31.9
30	180	33.0
31	186	34.1
32	192	35.2
33	198	36.3
34	204	37.4
35	210	38.5
36	216	39.6
37	222	40.7
38	228	41.8
39	234	42.9
40	240	44.0
41	246	45.1
42	252	46.2
43	258	47.3
44	264	48.4
45	270	49.5
46	276	50.6
47	282	51.7
48	288	52.8
49	294	53.9
50	300	55.0
51	306	56.1
52	312	57.2
53	318	58.3
54	324	59.4
55	330	60.5
56	336	61.6
57	342	62.7
58	348	63.8
59	354	64.9
60	360	66.0
61	366	67.1
62	372	68.2
63	378	69.3
64	384	70.4
65	390	71.5
66	396	72.6
67	402	73.7
68	408	74.8
69	414	75.9
70	420	77.0
71	426	78.1
72	432	79.2
73	438	80.3
74	444	81.4
75	450	82.5
76	456	83.6
77	462	84.7
78	468	85.8
79	474	86.9
80	480	88.0
81	486	89.1
82	492	90.2
83	498	91.3
84	504	92.4
85	510	93.5
86	516	94.6
87	522	95.7
88	528	96.8
89	534	97.9
90	540	99.0
91	546	100.1
92	552	101.2
93	558	102.3
94	564	103.4
95	570	104.5
96	576	105.6
97	582	106.7
98	588	107.8
99	594	108.9
100	600	110.0

PORTSMOUTH TO CAPE ANN

Mercator Projection
Scale 1:80,000 at Lat. 42°52'

North American Datum of 1983
(World Geodetic System 1984)

SOUNDINGS IN FEET
AT MEAN LOWER LOW WATER

Additional information can be obtained at nauticalcharts.noaa.gov.

TIDAL INFORMATION

PLACE		Height referred to datum of soundings (MLLW)		
NAME	(LAT/LONG)	Mean Higher High Water	Mean High Water	Mean Low Water
Portsmouth	(43°05'N/70°45'W)	feet 8.5	feet 8.1	feet 0.3
Gosport Harbor, Isles of Shoals	(42°59'N/70°37'W)	9.2	8.8	0.3
Hampton Harbor	(42°54'N/70°48'W)	9.0	8.6	0.3
Newburyport	(42°49'N/70°52'W)	8.5	8.1	0.3
Plum Island Sound (sound end)	(42°43'N/70°47'W)	9.3	8.9	0.3
Rockport	(42°40'N/70°37'W)	9.5	9.0	0.3

Dashes (---) located in datum columns indicate unavailable datum values for a tide station. Real-time water levels, tide predictions, and tidal current predictions are available on the Internet from <http://tidesandcurrents.noaa.gov>.
(Jul 2013)

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1)

Aids to Navigation (lights are white unless otherwise indicated):

AERO aeronautical	G green	Mo morse code	R TR radio tower
A alternating	IQ interrupted quick	N nun	Rct rotating
B black	iso isophase	OBSC obscured	s seconds
Bn beacon	LT HO lighthouse	OC occulting	SEC sector
C can	M nautical mile	Or orange	St M statute miles
DIA diaphone	m minutes	Q quick	VO very quick
F fixed	MICRO TR microwave tower	R red	W white
Fl flashing	Mkr marker	Ra Ref radar reflector	WHIS whistle
		R Bn radiobeacon	Y yellow

Bottom characteristics:

Blks boulders	Co coral	gy gray	Oys oysters	so soft
Bk broken	G gravel	h hard	PK rock	Sh shells
Cy clay	Grs grass	M mud	S sand	sy sticky

Miscellaneous:

AUTH authorized	Obstr obstruction	PD position doubtful	Subm submerged
ED existence doubtful	PA position approximate	Rep reported	
Wreck, rock, obstruction, or shoal swept clear to the depth indicated.			
(2) Rocks that cover and uncover, with heights in feet above datum of soundings.			
COLREGS International Regulations for Preventing Collisions at Sea, 1972.			
Demarcation lines are shown thus: ---			

HEIGHTS

Heights in feet above Mean High Water.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, and U.S. Coast Guard.

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 0.332" northward and 1.817" eastward to agree with this chart.

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 1. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 1st Coast Guard District in Boston, MA or at the Office of the District Engineer, Corps of Engineers in Concord, MA.

Refer to charted regulation section numbers.

CAUTION

Improved channels shown by broken lines are subject to shoaling, particularly at the edges.


CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

During some winter months or when endangered by ice, certain aids to navigation are replaced by other types or removed. For details see U.S. Coast Guard Light List.


FISHING AND HUNTING STRUCTURES

Uncharted fish and wildlife harvesting devices and structures such as fish traps, pound nets, crab traps, and duck blinds, some submerged, may exist in the area of this chart, particularly in the near shore area. Mariners should proceed with caution.



Portsmouth to Cape Ann
SOUNDINGS IN FEET - SCALE 1:80,000

13278



VHF Marine Radio channels for use on the waterways:

Channel 6 – Inter-ship safety communications.

Channel 9 – Communications between boats and ship-to-coast.

Channel 13 – Navigation purposes at bridges, locks, and harbors.

Channel 16 – Emergency, distress and safety calls to Coast Guard and others, and to initiate calls to other

vessels. Contact the other vessel, agree to another channel, and then switch.

Channel 22A – Calls between the Coast Guard and the public. Severe weather warnings, hazards to navigation and safety warnings are broadcast here.

Channels 68, 69, 71, 72 and 78A – Recreational boat channels.

Getting and Giving Help — Signal other boaters using visual distress signals (flares, orange flag, lights, arm signals); whistles; horns; and on your VHF radio. You are required by law to help boaters in trouble. Respond to distress signals, but do not endanger yourself.



NOAA Weather Radio All Hazards (NWR) is a nationwide network of radio stations broadcasting continuous weather information directly from the nearest National Weather Service office. NWR broadcasts official Weather Service warnings, watches, forecasts and other hazard information 24 hours a day, 7 days a week.

<http://www.nws.noaa.gov/nwr/>

Distress Call Procedures

- Make sure radio is on.
- Select Channel 16.
- Press/Hold the transmit button.
- Clearly say: "MAYDAY, MAYDAY, MAYDAY."
- Also give: Vessel Name and/or Description; Position and/or Location; Nature of Emergency; Number of People on Board.
- Release transmit button.
- Wait for 10 seconds — If no response Repeat MAYDAY call.

HAVE ALL PERSONS PUT ON LIFE JACKETS!

Quick References

Nautical chart related products and information	— http://www.nauticalcharts.noaa.gov
Interactive chart catalog	— http://www.charts.noaa.gov/InteractiveCatalog/nrnc.shtml
Report a chart discrepancy	— http://ocsddata.ncd.noaa.gov/idrs/discrepancy.aspx
Chart and chart related inquiries and comments	— http://ocsddata.ncd.noaa.gov/idrs/inquiry.aspx?frompage=ContactUs
Chart updates (LNM and NM corrections)	— http://www.nauticalcharts.noaa.gov/mcd/updates/LNM_NM.html
Coast Pilot online	— http://www.nauticalcharts.noaa.gov/nsd/cpdownload.htm
Tides and Currents	— http://tidesandcurrents.noaa.gov
Marine Forecasts	— http://www.nws.noaa.gov/om/marine/home.htm
National Data Buoy Center	— http://www.ndbc.noaa.gov/
NowCoast web portal for coastal conditions	— http://www.nowcoast.noaa.gov/
National Weather Service	— http://www.weather.gov/
National Hurricane Center	— http://www.nhc.noaa.gov/
Pacific Tsunami Warning Center	— http://ptwc.weather.gov/
Contact Us	— http://www.nauticalcharts.noaa.gov/staff/contact.htm



— For the latest news from Coast Survey, follow **@NOAAcharts**



This Booklet chart has been designed for duplex printing (printed on front and back of one sheet). If a duplex option is not available on your printer, you may print each sheet and arrange them back-to-back to allow for the proper layout when viewing.